



DESCRIPTION

- 1) EXTRUDED ALUMINIUM FRAME TYPE CONSTRUCTION.
- 2) POWDER COATED FINISH WHITE, AS STANDARD.
- 3) STANDARD COATING THICKNESS -60 MICRONS.
- 4) 20G GI BIRDSCREEN 1/2" x 1/2" PITCH.

1) THIS DRAWING IS A COPYRIGHT OF THE BALAJI AIRVENT,
IT IS NOT TO BE PRODUCED, COPIED, HANDED OVER TO
THIRD PARTY OR USED FOR ANY OTHER PURPOSE OTHER
THAN FOR WHITCH IT IS INTENDED.

2) THIS DRAWING IS TO BE READ & NOT SCALED.

TOLERANCES ON ALL DIMENSION = +3mm
ALL DIMENSIONS ARE IN MM
ALL TOLERANCES AS IS/INDUSTRY SPECIFICATONS

BALAJI AIRVENT PRODUCTS

24, AMRUT INDUSTRIAL ESTATE NO.1 K.T. INDUSTRIAL PARK,
GAURALIPADA, SECTOR-2, VALTHI, VASAI (EAST) DIST. THANE-401 208

TITLE

FRESH AIR LOUVER-BIRD SCREEN
MODEL : AVAFAL-BS

DRW.	DSGN.	RY	DRG. NO. :	AVAFAL-BS
DATE	SCALE	N.T.S	SHT 1 OF 1	REV. NO. : 00
20/08/2013				